


 Powered by Sterilight	 Powered by Sterilight	 Powered by Sterilight	 Powered by Sterilight
	<ul style="list-style-type: none"> Most popular, cost effective UV disinfection system for recommended flow rates up to 6 GPM (23 lpm) Designed for use in a smaller home or cottage 	<ul style="list-style-type: none"> Popular “work horse” disinfection system for recommended flow rates up to 10 gpm (38 lpm) Cost-effective unit is suitable for whole-home disinfection in the average residence 	<ul style="list-style-type: none"> NSF 55 Class B Certified version of the S5Q-PA Suitable for smaller applications, this system is NSF (B) validated for flow rates up to 3.6 gpm (13 lpm) 	<ul style="list-style-type: none"> NSF 55 Class B Certified version of the S8Q-PA Suitable for use in an average home, this system is NSF (B) validated for flow rates up to 7 gpm (26 lpm)
	IMPROVED WARRANTY	IMPROVED WARRANTY	IMPROVED WARRANTY	IMPROVED WARRANTY
PART NUMBERS				
N. America (NEMA P-15)	S5Q-PA	S8Q-PA	SV5Q-PA	SV8Q-PA
EU CEE (CEE 7/7)	S5Q-PA/2	S8Q-PA/2	--	--
AUS/NZ (AS 3112)	S5Q-PA/2A	S8Q-PA/2A	--	--
UK (BS 1363)	S5Q-PA/2B	S8Q-PA/2B	--	--
DINSINFECTON FLOW RATES				
	Flow rates based on 95% UVT water (70% UVT for NSF 55 certified systems)			
16 mJ/cm ²	11 GPM (42 lpm) (2.5 m ³ /hr)	19 GPM (72 lpm) (4.3 m ³ /hr)	3.6 GPM (13 lpm) (0.8 m ³ /hr)	7.0 GPM (26 lpm) (1.6 m ³ /hr)
30 mJ/cm ²	6 GPM (23 lpm) (1.4 m ³ /hr)	10 GPM (38 lpm) (2.3 m ³ /hr)	--	--
40 mJ/cm ²	4.5 GPM (17 lpm) (1.0 m ³ /hr)	8 GPM (29 lpm) (1.8 m ³ /hr)	--	--
SPECIFICATIONS				
Dimensions inch (cm)	22" x 2 1/2" (56.1 cm x 6.4 cm)	35 1/2" x 2 1/2" (90.4 cm x 6.4 cm)	22" x 2 1/2" (56.1 cm x 6.4 cm)	35 1/2" x 2 1/2" (90.4 cm x 6.4 cm)
Shipping Weight lbs (kg)	8 lbs (3.6 kg)	11 lbs (5 kg)	8 lbs (3.6 kg)	11 lbs (5 kg)
Connection Size	3/4" MNPT (/2B - BSP)	3/4" MNPT (/2B - BSP)	3/4" MNPT	3/4" MNPT
Power Consumption	30W	46W	30W	46W
REPLACEMENT PARTS				
Lamp/Quartz Sleeve Kit	S463-QL	S810-QL	S463-QL	S810-QL
UV Lamp Only	S463RL	S810RL	S463RL	S810RL
Quartz Sleeve Only	QS-463	QS-810	QS-463	QS-810
Controller	BA-ICE-S	BA-ICE-S	BA-ICE-S	BA-ICE-S
Sediment Cartridge	--	--	--	--
Carbon Cartridge	--	--	--	--

	 <p>Powered by Sterilight</p>	 <p>Powered by Sterilight</p>	 <p>Powered by Sterilight</p>	 <p>Powered by Sterilight</p>
	<ul style="list-style-type: none"> • Suitable for applications with water flow rates up to 9 gpm (34 lpm) • High output lamp technology allows for a more compact footprint without compromising performance 	<ul style="list-style-type: none"> • Powerful, compact UV disinfection system designed for the larger home or light commercial application • Recommended for flow rates up to 18 gpm (68 lpm) and available with UV sensor (VH410M - Home Plus section) 	<ul style="list-style-type: none"> • Adds integral 5 micron pre-filtration module to the VH200 UV system • Mounted on a reversible, heavy duty, painted steel bracket for installation flexibility and convenience 	<ul style="list-style-type: none"> • Adds integral 5 micron pre-filtration module to the VH410 UV system • Mounted on a reversible, heavy duty, painted steel bracket for installation flexibility and convenience
	IMPROVED WARRANTY	NEW	IMPROVED WARRANTY	NEW
PART NUMBERS				
N. America (NEMA P-15)	VH200	VH410	VH200-F10	VH410-F20
EU CEE (CEE 7/7)	VH200/2	VH410/2	VH200-F10/2	VH410-F20/2
AUS/NZ (AS 3112)	VH200/2A	VH410/2A	VH200-F10/2A	VH410-F20/2A
UK (BS 1363)	VH200/2B	VH410/2B	VH200-F10/2B	VH410-F20/2B
DISINFECTION FLOW RATES	Flow rates based on 95% UVT water (70% UVT for NSF 55 certified systems)			
16 mJ/cm ²	16 GPM (60 lpm) (3.6 m ³ /hr)	34 GPM (130 lpm) (7.8 m ³ /hr)	16 GPM (60 lpm) (3.6 m ³ /hr)	34 GPM (130 lpm) (7.8 m ³ /hr)
30 mJ/cm ²	9 GPM (34 lpm) (2.0 m ³ /hr)	18 GPM (70 lpm) (4.2 m ³ /hr)	9 GPM (34 lpm) (2.0 m ³ /hr)	18 GPM (70 lpm) (4.2 m ³ /hr)
40 mJ/cm ²	7 GPM (26 lpm) (1.6 m ³ /hr)	14 GPM (54 lpm) (3.3 m ³ /hr)	7 GPM (26 lpm) (1.6 m ³ /hr)	14 GPM (54 lpm) (3.3 m ³ /hr)
SPECIFICATIONS				
Dimensions inch (cm)	17 3/4" x 3 1/2" (45 cm x 8.9 cm)	23 1/2" x 3 1/2" (59.6 cm x 8.9 cm)	17" x 10 1/2" x 18" (43 cm x 26 cm x 45 cm)	17" x 10 1/2" x 28" (43 cm x 26 cm x 71 cm)
Shipping Weight lbs (kg)	12 lbs (5.4 kg)	17 lbs (7.7 kg)	26 lbs (11.8 kg)	32 lbs (14.5 kg)
Connection Size	3/4"- 1" MNPT COMBO (1/2B - BSP)	3/4"- 1" MNPT COMBO (1/2B - BSP)	1" MNPT INLET / 1" x 3/4" COMBO OUTLET (1/2B - BSP)	1" MNPT INLET / 1" x 3/4" COMBO OUTLET (1/2B - BSP)
Power Consumption	35W	60W	35W	60W
REPLACEMENT PARTS				
Lamp/Quartz Sleeve Kit	QL-200	QL-410	QL-200	QL-410
UV Lamp Only	S200RL-HO	S410RL-HO	S200RL-HO	S410RL-HO
Quartz Sleeve Only	QS-001	QSO-410	QS-001	QSO-410
Controller	BA-ICE-CL	BA-ICE-CL	BA-ICE-CL	BA-ICE-CL
Sediment Cartridge	--	--	CMB-510-HF	CMB-520-HF
Carbon Cartridge	--	--	--	--